




TYGER®

RISER®

TG-RS5T50167
TG-RS5T50168

PARTS LIST

- | | | |
|---|--|-----------------------------------|
| x1 Driver/left side Sidebar | x1 Passenger/Right Center Mounting Bracket | x12 8-1.25mm x 30mm Hex Bolts |
| x1 Passenger/right side Sidebar | x1 Driver/Left Rear Mounting Bracket | x12 8mm x 24mm x 2mm Flat Washers |
| x1 Driver/Left Front Mounting Bracket | x1 Passenger/Right Rear Mounting Bracket | x12 8mm Lock Washers |
| x1 Passenger/Right Front Mounting Bracket | x6 Plastic Bracket Covers | x12 8-1.25mm x 25mm Combo Bolts |
| x1 Driver/Left Center Mounting Bracket | x12 Retaining Clips | |



NOTE: (↑) represent location of the threaded inserts on the bottom of the sidebar.

NOTE: The Center Brackets have the mounting tabs facing opposite direction while the Rear Brackets have the mounting tabs facing the same direction. When installed correctly, all lower tabs will face towards the rear.



BEFORE INSTALLATION

READ INSTRUCTIONS CAREFULLY BEFORE STARTING INSTALLATION. REMOVE CONTENTS FROM BOX AND VERIFY ALL PARTS ARE PRESENT. FAILURE TO IDENTIFY DAMAGE BEFORE INSTALLATION COULD LEAD TO A REJECTION OF ANY CLAIM. IF MISSING PARTS OR ANY DAMAGE FOUND, PLEASE TAKE A PICTURE FOR THE CLAIM PURPOSE. PLEASE FILE YOUR CLAIM BY WWW.TYGERAUTO.COM/CONTACT

TORQUE VALUE




Fastener Size	Class 8.8 Torque (ft-lbs)	Class 10.9 Torque (ft-lbs)
6mm	6-7	6-7
8mm	15-16	22-23
10mm	31-32	44-45
12mm	54-55	78-79
14mm	87-88	125-126

NOTE

Use illustration to identify brackets and running boards.

STEP 1

Starting on the passenger side, front of the vehicle, remove the plastic plugs or hex bolts covering the (2) threaded holes in the body panel, (Fig 1). Select the passenger side Front Mounting Bracket, (Fig 2). Attach the Bracket to the vehicle using the included (2) 8mm Hex Bolts, (2) 8mm Lock Washers and (2) 8mm Flat Washers, (Figs 2-3). Do not tighten hardware at this time.





TYGER[®]


STEP 2

Select (1) Plastic Bracket Cover and (2) Retaining Clips. Slide the Cover over the passenger/right front Bracket. Line up the (2) mounting holes in the Cover with the holes in the Bracket. Insert the Clip into the holes and push center pin to expand Clip, (Figs 4-5). Repeat this Step for all Cover installations. Notes install the plastic covers onto the brackets before installing the side bar.


STEP 3

Next, move to the center mounting location, (Fig 6).


NOTE: Installation will use the 1st, 2nd & 4th mounting locations for the Mounting Brackets.



(Fig 4) Slide Cover over top of Bracket. Attach Cover to Bracket with (2) Retaining Clips



(Fig 5) PS Front Bracket with cover installed




(Fig 6) Passenger/right center mounting location



STEP 4


Select the passenger side Center Mounting Bracket, (Fig 7).

IMPORTANT: The Center and Rear Brackets look similar but each one is unique. Use the illustration above and Fig 7 to help identify each Bracket. Repeat Steps 1-2 to install the Passenger side Center Bracket, (Figs 8-9).




(Fig 7) Passenger/right Center & Rear Brackets

NOTE: The Center Bracket has the mounting tabs facing opposite direction while the Rear Bracket has the mounting tabs facing the same direction. When installed correctly, all lower tabs will face towards the rear.



(Fig 8) Passenger/right Center Bracket installed



(Fig 9) PS Center with Cover installed






TYGER[®]

STEP 5

Continue to the last mounting location at the back of the cab, (Fig 10). Repeat Steps 1-2 to install the Passenger side Rear Bracket, (Figs 11-12).

STEP 6


Once all (3) Mounting Brackets have been fully installed, carefully unwrap the Passenger/right Sidebar. Use the illustration above to help determine the correct Sidebar. Place the Sidebar on top of the (3) Mounting Brackets.






STEP 7


Attach the Sidebar to the Mounting Brackets with the included (6) 8mm Combo Bolts, (Figs 13-16). Do not tighten at this time.




(Fig 13) Passenger/right Sidebar attached to Front Bracket illustrated



(Fig 15) Passenger/right Sidebar attached to PS Center Bracket



(Fig 14) Passenger/right Sidebar attached to PS Front Bracket



(Fig 16) Passenger/right Sidebar attached to PS Rear Bracket



TYGER[®]

STEP 8

Level and adjust the Sidebar as desired and tighten all hardware.

STEP 9

Repeat Steps 2-8 for Driver/left Sidebar installation.

STEP 10

Do periodic inspections to the installation to make sure that all hardware is secure and tight.

