

RISER

TG-RS9C50248

BEFORE INSTALLATION

READ INSTRUCTIONS CAREFULLY BEFORE STARTING INSTALLATION. REMOVE CONTENTS FROM BOX AND VERIFY ALL PARTS ARE PRESENT. FAILURE TO IDENTIFY DAMAGE BEFORE INSTALLATION COULD LEAD TO A REJECTION OF ANY CLAIM. IF MISSING PARTS OR ANY DAMAGE FOUND, PLEASE TAKE A PICTURE FOR THE CLAIM PURPOSE. TO FILE YOUR CLAIM, PLAESE VISIT: WWW.TYGERAUTO.COM/CONTACT

Fastener Size	Class 8.8 Torque (ft-lbs)	Class 10.9 Torque (ft-lbs)
6mm	6-7	6-7
8mm	15-16	22-23
10mm	31-32	44-45
12mm	54-55	78-79
14mm	87-88	125-126

PARTS LIST

x1 Driver/left Sidebar

x1 Passenger/right Sidebar

x8 Mounting Brackets

x8 Plastic Bracket Covers


x16 Retaining Clips (use with Plastic Covers)

x16 8-1.25mm x 30mm Hex Bolts

x16 8-1.25mm x 25mm Combo Bolts

x16 8mm Lock Washers

x16 8mm x 24mm x 2mm Flat Washers




Customer Support: www.TygerAuto.com/Contact


PROCEDURE


REMOVE CONTENTS FROM BOX. VERIFY ALL PARTS ARE PRESENT. READ INSTRUCTIONS CAREFULLY BEFORE STARTING INSTALLATION. ASSISTANCE IS RECOMMENDED.





Start the installation under the passenger/right of the vehicle. Locate the 6 plugs along the bottom edge of the body. Mounting Brackets will bolt to the 1st, 3rd, 4th and 6th threaded mounting holes, (Figures 1—6). Remove the plastic plugs from each mounting location. Directly above each threaded insert is a top mounting location on the side of the body panel. Hold a Bracket up in place to help determine the correct mounting holes to use along the body. NOTE: Thread an 8mm Hex Bolt into the threaded inserts to clear paint as required.



















Select (1) Mounting Bracket. Starting at the front, bolt the Mounting Bracket to the factory threaded holes with (2) 8mm Hex Bolts, (2) 8mm Lock Washers and (2) 8mm Flat Washers, (Figures 7 & 8). Do not tighten hardware at this time. Repeat this Step to install remaining (3) Mounting Brackets on the remaining mounting locations along the body panel.









STEP 3


Select (1) Plastic Bracket Cover. Slide Plastic Cover over Bracket, (Figures 9). Line up the (2) mounting holes in the Cover with the side holes in the Bracket. Insert (1) Plastic Clip into each hole and push center pin to expand Clip. Repeat this Step for (3) remaining plastic covers, (Figures 9—13).


Notes: please install all plastic covers onto the brackets before installing the side bar.














STEP 4


Select the passenger/ right Sidebar. Use the illustration above to help determine the correct Sidebar. Place the Sidebar on top of the Brackets. IMPORTANT: Do not slide, (front to back), the Sidebar on the Brackets or damage to the finish may result.



3rd Bracket



(Fig 14) Sidebar attached to the Passenger **Front Bracket**



(Fig 17) Sidebar attached to the Passenger Rear **Bracket**

